



Code: 9900105096

Features:

- Low maintenance sealed unit
- Gel filled reference cell
- BNC connection with Boot plastic Cover
- Cable length 6 meters
- Pellon Diaphragm high accuracy

Field Application:

- General laboratory
- Drinking Water
- Swimming pools
- Water monitoring and control plan

Features:

- Range: pH 2÷12
- Temperature: 0÷60 °C
- Pressure: 6 Bar
- Trasparent plastic Body
- **Single junction** with KCL Gel and **Pellon diaphragm**.
- BLUE cup with **6 meters cable** size 3mm, BNC plug included with blue Boot cup.
- Batch production with 4 number to indicate Week and Year production.
- Single Package with neutral carton box.
- Neutral Label.

TECHNICAL CHARACTERISTICS

pH Range:	2 ÷ 12
Min. Conductivity:	50 µS/cm
Temp. Range:	60° C
Pressure Range:	up to 6 bar
Body material:	Epoxy
Membrane material:	Glass
Diaphragm type:	Pellon
Mechanical Mounting:	Ø 12
Electrical Connection:	6 m cable + BNC (Blue BOOT Cup)
Reference:	GEL
Offset:	12 mV
Gain:	97% of theoretical or higher
Storage temperature	+2 ÷ 50 °C (do not freeze)

DIMENSIONS

