

Hardware Fittings — Ductile Iron

A
3

Socket Eye

Product Data (continued)

Catalog Number	Ultimate Strength lb (kN)	Dimensions Inches (mm)				Approx Wt Each lb (kg)
		W	R	L	Diameter	
SA22	30,000 (133)	2¼ (57.2)	1¾ (20.6)	2¼ (52.4)	1¼ (17.5)	1.85 (.84)
SA1013	30,000 (133)	1 (25.4)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	1.50 (.68)
SA10.513	30,000 (133)	1¼ (27)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	1.30 (.50)
SA1113	30,000 (133)	1½ (28.6)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	1.50 (.68)
SA1313	30,000 (133)	1¾ (34.9)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	1.75 (.79)
SA1417	30,000 (133)	1½ (38.1)	1 (25.4)	2½ (63.5)	1¼ (27)	1.75 (.79)
SA1613	30,000 (133)	1¾ (44.5)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	1.85 (.84)
SA16054	30,000 (133)	1¾ (44.5)	1¾ (20.6)	5½ (139.7)	1¼ (17.5)	2.10 (0.95)
SA2113	30,000 (133)	2⅛ (54)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	2.00 (.91)
SA2213	30,000 (133)	2¼ (57.2)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	2.00 (.91)
SA24	30,000 (133)	2½ (63.5)	1¾ (20.6)	2¼ (52.4)	1¼ (17.5)	2.34 (1.09)
SA2413	30,000 (133)	2½ (63.5)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	2.25 (1.02)
SA2613	30,000 (133)	2¾ (69.9)	1¾ (20.6)	2¼ (52.4)	1¾ (20.6)	2.85 (1.29)
909662000 ⁽¹⁾	50,000 (222)	1¼ (27)	1½ (28.6)	5½ (139.7)	1¼ (27)	5.8 (2.63)
909642000 ⁽¹⁾	50,000 (222)	1¾ (30.2)	1½ (28.6)	5½ (139.7)	1¾ (20.6)	5.3 (2.40)
909672000 ⁽¹⁾	50,000 (222)	1¾ (31)	1½ (28.6)	5½ (139.7)	1¾ (30.2)	5.6 (2.54)
909622000 ⁽¹⁾	50,000 (222)	1¾ (36.5)	1½ (28.6)	5½ (139.7)	1¾ (30.2)	5.8 (2.63)
909612000 ⁽¹⁾	50,000 (222)	1½ (38.1)	1½ (28.6)	5½ (139.7)	1¾ (20.6)	6.0 (2.72)

NOTE: For use with class 52-3 and 52-5 insulators per ANSI Spec. C-29.2-71.

⁽¹⁾ For use with class 52-8 and 52-11 insulators per ANSI Spec. C-29.2-71.