GAS-Mate®

COMBUSTIBLE GAS LEAK DETECTOR

Safely detect combustible gas and flammable refrigerant leaks.





		0	
9			
200		Progress	
	act for		1
		93V 120M	

SPECIFICATIONS	
Includes	GAS-Mate Combustible gas sensor Two D-size alkaline batteries Carrying case
Compatible refrigerants	Propane (R290), isobutane (R600a), R441a, hydrogen for- ming gas (95/5), natural gas, methane, ammonia, and more
Sensitivity	5 ppm for methane, propane (R290), isobutane (R600a), and hydrogen 1 ppm for gasoline
Power source	Two D-size alkaline batteries (use Duracell® MN1300 to maintain intrinsically safe approval)
Battery life	25 hours
Weight	1.54 lb. (700 g)
Certifications	Intrinsically safe for Class I, Division I, Groups A - D, T4 and II 3G Ex nA nL IIC T4 X as per MET Laboratories Listing #E112145 CE, UKCA
Probe length	15 in. (38 cm)
Warranty	Three-year over-the-counter

ORDERING INFORMATION			
718-202-G1			
eplacement Parts			
706-700-G1			
718-701-G1			
	718-202-G1 eplacement Parts 706-700-G1		

ADVANTAGES

- Detects natural gas, propane, isobutane, ammonia, hydrogen forming gas (95/5), and more
- Ultimate sensitivity of 5 ppm for methane, R290 (propane), and R600a (isobutane)
- Intrinsically safe for use in combustive/ explosive environments
- Great for flammable refrigerants like R290, R600a, and R441a
- Runs on two D-cell batteries

www.inficonservicetools.com | service.tools@inficon.com 11