

Intermediate Piece - Stainless Steel 304L

INFICON CF quality fittings are manufactured according to ISO 3669 and the latest TS/ ISO 3669-2 standard. INFICON Ultra high vacuum fittings are designed for applications down to 1×10^{-12} mbar and bakeout temperatures up to 400°C.



BENEFITS

- World wide logistics
- Design and measures follow strictly international respected standards
- Surface finish, welds, material specifications and cleanliness meet or exceed specifications
- 2011/65/EU RoHS compliant


ORDER INFORMATION

Type	DN 16 CF	DN 40 CF	DN 63 CF	DN 100 CF	DN 160 CF
Intermediate piece DN 100 CF				213-204	
Intermediate piece DN 16 CF	213-201				
Intermediate piece DN 160 CF					213-205
Intermediate piece DN 40 CF		213-202			
Intermediate piece DN 63 CF			213-203		

SPECIFICATIONS

Type	DN 16 CF	DN 40 CF	DN 63 CF	DN 100 CF	DN 160 CF
Dimension A	76	126	210	270	334
Dimension B	0.5	1	1	1	1.5
Dimension C	0.5	1	1	1	1.5
Dimension D	16	37	66	104	155
Material:	Stainless steel 304L / 1.4306				

DIMENSIONS



www.inficon.com reachus@inficon.com

Due to our continuing program of product improvements, specifications are subject to change without notice. RateWatcher is a trademark of INFICON. All other trademarks are the property of their respective owners.

(2018-08) © 2018 INFICON